

CPS Aluminum Compression platen

- Soft samples, cardboards, plastics, etc.
- Aluminum anodized
- Temperature range: -70°C - +180°C
- Max capacity depends on the size of coupling
- Scope of supply 1 pair

Item number	Dimensions	Weight/each platen
CPS-50	50 x 50mm	0.20 kg
CPS-100	100 x 100mm	0.52 kg
CPS-120x120	120 x 120mm	0.78 kg
CPS-120x180	120 x 180mm	1.14 kg
CPS-125x250	125 x 250mm	1.73 kg
CPS-150	150 x 150mm	1.23 kg
CPS-150x300	150 x 300mm	2.35 kg
CPS-200	200 x 200mm	2.10 kg
CPS-250	250 x 250mm	3.40 kg
CPS-300	300 x 300mm	4.35 kg
CPS-350	350 x 350mm	6.60 kg
CPS-400	400 x 400mm	8.70 kg
CPS-400x600	400 x 600mm	13.40 kg
CPS-500	500 x 500mm	14.00 kg

Further dimensions and versions on request



CPS-St Steel Compression platen

- Hard materials, steel, plastics, stone etc.
- Hardened steel 58HRC
- Temperature range: 0°C - +350°C
Nickel plated: -70°C - +350°C (on request)
- Max capacity depends on the size of coupling
- Scope of supply 1 plate

Item number	Dimensions	Weight
CPS-100-St	100 x 100mm	1.54 kg
CPS-196-St	196 x 196mm	6.60 kg
CPS-246-St	246 x 246mm	10.40 kg
CPS-296-St	296 x 296mm	13.60 kg
CPS-396-St	396 x 396mm	33.00 kg
CPS-396x496-St	396 x 496mm	41.00 kg
CPS-396x596-St	396 x 596mm	50.00 kg

Further dimensions and versions on request



CPS-L Aluminum plate

- Perforated platen suitable for foam testing. The platen is perforated to allow air to escape
- Aluminum anodized
- Diameter of holes: 6 mm spaced 20 mm
- Temperature range : 0°C - +180°C
- Max capacity depends on the size of coupling
- Scope of supply 1 plate

Item number	Dimensions	Weight
CPS-120-L6x20	120 x 120mm	0.74kg
CPS-150-L6x20	150 x 150mm	1.10kg
CPS-150x220-L6x20	150 x 220mm	1.68kg
CPS-400-L6x20	400 x 400mm	8.20 kg

Further dimensions and versions on request

